

远程数据采集系统（选配）
Remote data collection system(optional)

LSSX



故障率数据
Failure rate data

产能数据
Capacity data

使用率数据
Usage data

钢丝规格（耗材）
Steel wire specification (consumables)



GS01
标准版 折弯钢丝（大头）
应对7~8MM孔眼
Standard edition
bending steel wire(large head)
Coping with 7-8mm hole



GS02
专用版 折弯钢丝（小头）
应对5~6MM孔眼
Special edition
bending steel wire(Small head)
Coping with 5-6mm hole

技术参数 | Technical parameters

型号 Model	项目 Project	参数 Parameter
LS6021/CA	电压 Voltage	220V 50~60Hz
	气压 Barometric pressure	0.4-0.6MPa
	功率 Power	0.7KW
	外形尺寸 Dimensions	1250*600*1650mm
	装箱尺寸 Packing size	1350*740*1280mm
	净重 Net weight	140kg
	毛重 Gross weight	150kg

*以上型号仅供参考，详细情况请咨询。
The above types are only for reference, and you can consult local distributors for details.

*为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.

LS6021CA

帽绳机
Cap rope machine

LENSH

浙江凌志智能科技有限公司
ZHEJIANG LENSH INTELLIGENT TECHNOLOGY CO.,LTD.

地址：宁波市海曙区光文路500号 电话(TEL)：0574-8742 3969 0574-8388 5719
Address:No 500 RD Guangwen District Haishu Ningbo Zhejiang,China E-mail: wuhanqiao66@163.com web:www.lensh.cn

CE

LENSH®

应用范围 | Application

适用拉链带帽衫、套头风帽衫等帽绳穿绳工艺
Apply zippered hoodie, hoodie and other hood rope wearing technology



应用工艺 | Application process

应对不同工艺之创新技术
Innovative technologies for different processes

自适应尺码大小
Adaptive size



托料杆
Feeding rod



拉链夹爪器
Zipper clip clawer



规格范围 | Specification range



适用孔眼
Applicable hole



适用带绳
Suitable for rope



效率分析 | Efficiency analysis

80~180%

Before 20~32s



人工作业劳动强度大 效率低
Manual work quickly tired and low efficiency

After 12~14s



自动化设备作业，低疲劳度、效率高
Automated equipment operation, low fatigue, high efficiency