

技术参数 | Technical parameters

型号	Model	LS8191
电压	Voltage	220V 50-60Hz
气压	Air pressure	0.4-0.6MPa
功率	Power	2.3Kw
外形尺寸	Dimensions	1130*640*1500mm
装箱尺寸	Packing size	1230*710*1600mm
净重	Net weight	150Kg
毛重	Gross weight	180Kg

*以上型号仅供参考，详细情况请咨询。
The above types are only for reference, and you can consult local distributors for details.

*为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.

LS8191

折标机
Folding machine



浙江凌志智能科技有限公司
ZHEJIANG LENSH INTELLIGENT TECHNOLOGY CO.,LTD.

地址：宁波市海曙区光文路500号 电话(TEL)：0574-8742 3969 0574-8388 5719
Address:No 500 RD Guangwen District Haishu Ningbo Zhejiang,China E-mail: wuhanqiao66@163.com web:www.lensh.cn



应用范围 | Application

适用卷装商标切断对折压平
Suitable for roll trademark cut-off folding flat



应用工艺 | Application process

应对不同工艺之创新技术及选配组件
Innovative technologies and optional components for different processes



色标感应器（标配）
Standard color label sensor (standard)



稳定 便利
Stable and convenient.


远程数据采集系统（选配）
Remote data collection system(optional)

LSSX



故障率数据 Failure rate data
产能数据 Capacity data
使用率数据 Usage data

规格范围 | Specification range




折边宽度：15mm~40mm

效率分析 | Efficiency analysis

300% ↑

传统作业 9S
Traditional jobs



PLC程控折标机 3S
Program-controlled folding machine.



依据材料特性，不同程序应对
Depending on the material characteristics, different procedures should be handled